



SterileRight

SterileRight Packaging MFG. Inc.

1F, No. 33-7, Dahua 2nd RD., Qidu Dist., Keelung 206, Taiwan

Tel: +886-2-2455-5498 Fax: +886-2-2455-5497

E-mail: service@sterileright.com.tw

TECHNICAL DATA SHEET

DOC NO. : TDS.261.11

DATE: Jul. 06, 2016

PRODUCT : HDPE Film

VERSION: 1.0

MATERIAL DESCRIPTION : HDPE FILM 90um

SPECIFICATION:

Properties		Test method	Unit	value
Thickness			µm	80-100
Static C.O.F.	MD	ASTM D-1894-01	--	0.15~0.35
	CD			0.15~0.35
Kinetic C.O.F.	MD		--	0.15~0.35
	CD			0.15~0.35
Tensile strength	MD	ASTM D-882-02	kgf/cm ²	>400
	CD			>400
Elongation	MD		%	>150
	CD			>150

STANDARD: Complies with the ISO11607-1.

SEALING: Sealing parameters are depended on the type of sealing machine.

STERILIZATION: Suitable for Steam(121°C,30minutes), EtO or Irradiation.

STORAGE: Store in a cool, dry and clean place. Keep away from direct sunlight.

EXPIRY: 5 YEARS